

# Rollfix 80/100 crank

## Large format projection with no electrical installation

- · Removable hand crank prevents unauthorised use
- · User friendly thanks to smooth-running crank drive (at the right side)
- · Projection surface continuously adjustable
- Wall or ceiling mounting possible, supplied with universal mounting attachment
- Square steel casing (diameter 10 x 10 cm)
- . Casing colour: white, RAL 9010
- · Suitable for installation into suspended ceilings with accessories

## Screen surface

- · Front projection, Type D
- · Gain factor according to DIN 19045, approx. 1.2
- · Matt white, on a woven base • Rear side: black

- Front projection, Type S
- · Gain factor according to DIN 19045, approx. 2,2 . Mother-of-pearl tint, on a woven base
- Rear side: black



### Accessories

Wall/Ceiling spacer (without ill.) Space to wall/ceiling approx. 40 cm Code No. 8585WW1034



exactly in the casing thanks to a circular weight slat

## Mounting set for suspended ceilings (without ill.)

This set allows the screen to be mounted into suspended ceilings (up to 100 cm) Code No. 8585WW1038



15/30/50 cm Code No. 8585WW1038

7		1	7
		ı	
-	В		-
6		Ļ	6

External Dimensions approx. WxH in cm	Diagonal cm/inch	Weight in kg approx.	Surface	Code No.
180 x 180	255/100	17,5	Typ D	3034NA8001
200 x 150	238/ 94	20,0	Typ D	3034PB8001
200 x 200	283/111	20,5	Typ D	3034PA8001
240 x 240	339/134	25,0	Typ D	3034RA8001
270 x 270	382/150	27,5	Typ D	3034UA8001
300 x 250	391/154	29,0	Typ D	3034VD8001
300 x 300	424/167	29,5	Typ D	3036VA8001
200 x 200	283/111	20,5	Typ S	3134PA8008
240 x 240	339/134	11,0	Typ S	3134RA8001
300 x 300	424/167	14,0	Typ S	3136VA8001

ns are available upon request. Also, mounting frames or installation housing such as the Rollfix Electric 80/100 are available upon request.